



# LIGHTS THERE

# BRILLED LIGHTING

## LED Anti-Glare Cellular Tunable Recessed Down Light



### FEATURES

- 2"- 9"
- 5W-55W
- Multi CCT
- 50,000 hours lifetime
- Controls

### CONSTRUCTION:

Downlight body and endcaps are both fabricated from aluminum for maximum rigidity. Lens crafted with high quality polymer. Spring clips for easy installation.

### OPTICAL SYSTEM:

Anti-glare lens. 24°, 36°, 60° beam angle options.

### WARRANTY:

5-year limited warranty. Actual performance may differ as a result of end-user environment and application.

### ELECTRICAL:

Uses a -20°C to 40°C (-4°F to 104°F) case temperature drive. Available as 110-277V input.

### DIMMING:

Dimmable range from 0-10V.

Power	Size	Beam angle
5-8W	62mm*H59	24° 36° 60°
8-10W	75mm*H62	24° 36° 60°
10-12W	85mm*H64	24° 36° 60°
15-18W	105mm*H72	24° 36° 60°
18-22W	130mm*H73	24° 36° 60°
25-35W	170mm*H80	24° 36° 60°
30-45W	195mm*H85	24° 36° 60°
40-55W	235mm*H95	24° 36° 60°



Before Non LED



After Anti-Glare LED



24° Beam Spread



60° Beam Spread